## AMENDMENTS TO THE CLAIMS

## 1-13. (Cancelled)

- 14. (Previously presented) A process for the manufacture of a polystyrene closed-cell foam in which a which comprises extruding a blend of polymer and a blowing agent to obtain the polystyrene closed cell foam wherein said blowing agent comprising 1,1-difluoroethane, 1,1,1,2-tetrafluoroethane and optionally an additive is employed and said blowing agent comprising more than 80% by weight of 1,1-difluoroethane and 1,1,1,2-tetrafluoroethane and in which the weight ratio of 1,1-difluoroethane to 1,1,1,2-tetrafluoroethane in the blowing agent is at most 4.
- 15. (Previously presented) The process according to Claim 14, in which the weight ratio of 1,1-difluoroethane to 1,1,1,2-tetrafluoroethane in the blowing agent is at least 1.5.
- 16. (Previously presented) The process according to Claim 15, in which the weight ratio of 1,1-difluoroethane to 1,1,1,2-tetrafluoroethane in the blowing agent is more than 2.
- 17. (Currently amended) The process according to Claim 14, in which the blowing agent contains more than 60% than 90% by weight of a mixture of 1,1-difluoroethane and 1,1,1,2-tetrafluoroethane.
- 18. (Previously presented) The process according to Claim 14, wherein said additive is alcohol.
- 19. (Previously presented) A composition comprising 1,1-diffuoroethane and 1,1,1,2-tetrafluoroethane and an alcohol, which composition can be used as blowing agent for the manufacture of polymer-based foams.

2

636999

- 20. (Previously presented) The composition according to Claim 19, wherein said alcohol is methanol, ethanol, n-propanol or isopropanol.
- 21. (Currently amended) A composition comprising 1,1-difluoroethane, 1,1,1,2-tetrafluoroethane and carbon dioxide, wherein the weight ratio of 1,1-difluoroethane to 1,1,1,2-tetrafluoroethane in the blowing-agent composition is greater than 1 and at most 4, which can be used as blowing agent for the manufacture of polymer-based foam and said composition comprises more than 80% by weight of 1,1-difluoroethane and 1,1,1,2-tetrafluoroethane.
- 22. (Previously presented) The composition according to Claim 19, in which the weight ratio of 1.1-difluoroethane to 1,1,1,2-tetrafluoroethane is at least 1.5.
- 23. (Previously presented) The composition according to Claim 19, containing more than 60% by weight of 1,1-difluoroethane and of 1,1,1,2-tetrafluoroethane.
- 24. (Previously presented) A thermal insulation panel comprising the polystyrene closed-cell foam, obtained using the process according to Claim 14.
- 25. (Previously presented) A thermal insulation panel comprising the polystyrene closed-cell foam, obtained using the process according to Claim 16.
- 26. (Previously presented) A thermal insulation panel comprising the polystyrene closed-cell foam, obtained using the process according to Claim 17.
- 27. (Previously presented) The process according to Claim 14, wherein the polystyrene closed-cell foam contains more than 90% of closed cells.

- 28. (Previously presented) The process according to Claim 27, wherein the thermal conductivity at 10°C of the polystyrene closed-cell foam after 90 days storage at room temperature is 27.0 mW/m.K or less.
- 29. (Previously presented) The thermal insulation panel according to Claim 24, wherein the polystyrene closed-cell foam contains more than 90% of closed cells.
- 30. (Previously presented) The thermal insulation panel according to Claim 24, wherein the thermal conductivity at 10°C of the polystyrene closed-cell foam after 90 days storage at room temperature is 27.0 mW/m.K or less.
- 31. (Previously presented) The thermal insulation panel according to Claim 29, wherein the thermal conductivity at 10°C of the polystyrene closed-cell foam after 90 days storage at room temperature is 27.0 mW/m.K or less.
- 32. (Previously presented) The composition according to Claim 21, in which the weight ratio of 1,1-difluoroethane to 1,1,1,2-tetrafluoroethane is at least 1.5.
- 33. (Previously presented) The composition according to Claim 21, in which the weight ratio of 1,1-difluoroethane to 1,1,1,2-tetrafluoroethane is at least 2.3.
- 34. (Currently amended) The composition according to Claim 21, containing wherein the composition contains more than 90% than 60% by weight of 1,1-diffuoroethane and of 1,1,1,2-tetrafluoroethane.
- 35. (New) The process as claimed in claim 14, in which the weight ratio of 1,1-difluoroethane to 1,1,1,2-tetrafluoroethane in the blowing agent is at most 3.5.

4

636999

Application No. 10/070,979 Reply to Office Action of April 3, 2008

36. (New) A blowing agent composition comprising 1,1-diffuoroethane, 1,1,1,2-tetrafluoroethane and carbon dioxide, wherein the weight ratio of 1,1-diffuoroethane to 1,1,1,2-tetrafluoroethane in the blowing agent is greater than 1\_and at most 4 said blowing agent comprising more than 80% by weight of 1,1-diffuoroethane and 1,1,1,2-tetrafluoroethane.